


TECHNICAL SPECIFICATION - TABULAR

‘Supply of items for foreign materials exclusion control in equipment disassembled for maintenance’.

No.	Name		Technical data	Color	Quantity (Unit of measurement eng)/Unit of measurement bg
1.	FME Disposable covers		4in (100mm) Diameter	OR orange	1 PK 50 PK
2.	FME Disposable covers		8in (200mm) Diameter	OR orange	1 PK 50 PK
3.	FME Disposable covers		12in (300mm) Diameter	OR orange	1 PK 25 PK
4.	FME Tarp		These tarps are the answer to larger area FME controls with document pockets for traceability 3m x 3m	OR orange	3 pcs (Each)
5.	FME Magnetic Round Covers		Diameter– 66cm	OR orange	1 pcs (Each)
6.	FME Magnetic Round Covers		Diameter– 81 cm	OR orange	1 pcs (Each)

7.	FME Magnetic Mesh Round Covers		Diameter 55 cm	OR orange	1 pcs (Each)
8.	FME Magnetic Mesh Round Covers		Diameter 76 cm	OR orange	1 pcs (Each)
9.	FME Magnetic Mesh Round Covers		Diameter 90 cm	OR orange	1 pcs (Each)
10.	Stanchions		Highly visible barriers clearly warn of hazardous areas and help prevent accidents. Extremely durable and resistant to tough wear & tear. The stanchions are with Retractable-Belt Posts with belt length 304 cm	Yellow stanchion, yellow black striped tape	12 PK 4 PK
11.	FME Secure Document Pouches		Document pouches can be used in portrait or landscape position. Made with a heavy duty hook and loop closure strap. Constructed of Fire Retardant material certified to NFPA 701 Test Method 2 and meets NFPA 805 requirements. Available in Orange (OR), Red (R), and Pink (PK).	OR orange	50 pcs (Each)



12.	Tether Tape		Heavy duty tape conforms to the shape of whatever it is applied to. Made from self-fusing silicone rubber that leaves no adhesive residue behind. Inner fiberglass webbing increases the strength and makes the tape resistant to sharp objects.	Yellow	2 PK 10 PK
13.	Heat Shrink		Tether tape to protect them from abrasive and harsh working environments. Size reduces by 200% when heat or cold is applied. Size 1"x1.75"	OR orange	1 PK 25 PK
14.	Heat Shrink		Tether tape to protect them from abrasive and harsh working environments. Size reduces by 200% when heat or cold is applied. Size 1"x1.75"	OR orange	1 PK 25 PK
15.	Heat Shrink		Tether tape to protect them from abrasive and harsh working environments. Size reduces by 200% when heat or cold is applied. Size 1"x1.75"	OR orange	1 PK 25 PK
16.	D-Rings		D-Rings are used to support tools weighing 5 pounds or less by providing secure attachment points with limited surface area. The D-	OR orange	1 PK (100 PK)



			Ring provides a strong attachment without inhibiting the tools use. Size 1.2cm x 5.7cm		
17.	D-Rings		D-Rings are used to support tools weighing 5 pounds or less by providing secure attachment points with limited surface area. The D-Ring provides a strong attachment without inhibiting the tools use. 2.54cm x 8.89cm	OR orange	1 PK (100 PK)
18.	D-Rings		D-Rings are used to support tools weighing 5 pounds or less by providing secure attachment points with limited surface area. The D-Ring provides a strong attachment without inhibiting the tools use. 2.54cm x 30.5cm	OR orange	1 PK (100 PK)
19.	V-Rings		V-Ring attachments are optimized to support heavier tools with max load ratings up to 80 LBS (36.3 KG). Size 2.5cm x 35.5cm	OR orange	1 PK 10 PK



20.	Coil Tethers		Hook to Hook Coil Tether with Two Swivels. Coil Tethers for drop prevention, built to be durable and practical. Coils allow for a compact design that remains close to the body, giving the user more control over the attached tools, while the vinyl coating makes these tethers easy to clean. The non-conductive allows for use in a wider range of environments.	OR orange	1 PK 10 PK
21.	Wristband Paracord With Attachment Points		High-Visibility orange paracord with barrel lock adjustment feature. Attachments include an extra barrel lock, clip, or clamp.	OR orange	30 pcs (Each)
22.	Floating eyewear retainers		Floating retainers suitable for almost all eyewear frames, making the product stay securely on the surface	Yellow	50 pcs (Each)
	Floating eyewear retainers			Yellow	50 pcs (Each)



23.	FME Outdoor Storage & Warehouse Covers			UV resistant, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 25 mm	OR orange	10 pcs (Each)
24.	FME Outdoor Storage & Warehouse Covers			FME Outdoor Storage & Warehouse Covers UV resistant,, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 50 mm	OR orange	10 pcs (Each)
25.	FME Outdoor Storage & Warehouse Covers			UV resistant, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 100 mm	OR orange	10 pcs (Each)
26.	FME Outdoor Storage & Warehouse Covers			UV resistant, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 150 mm	OR orange	10 pcs (Each)

27.	FME Outdoor Storage & Warehouse Covers			UV resistant, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 200 mm	OR orange	10 pcs (Each)
28.	FME Outdoor Storage & Warehouse Covers			UV resistant, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 250 mm	OR orange	5 pcs (Each)
29.				FME Outdoor Storage & Warehouse Covers UV resistant,, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 300 mm	OR orange	5 pcs (Each)
30.				FME Outdoor Storage & Warehouse Covers UV resistant,, fire retardant, waterproof, and easily decontaminated or cleaned. Temperature Rating: 160°F (71° C) Continuous 180°F (82°C) Size 381 mm	OR orange	1 pcs (Each)

31.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=11mm, B=12mm, C=9mm, D=10mm, E=10mm, F=16mm	OR orange	1 PK (100 PK)
32.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=12mm, B=14mm, C=10mm, D=12mm, E=11mm, F=18mm	OR orange	1 PK (100 PK)


33.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=18mm, B=21mm, C=17mm, D=19mm, E=15mm, F=25mm	OR orange	1 PK (100 PK)
34.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=23mm, B=26mm, C=21mm, D=25mm, E=18mm, F=29mm	OR orange	1 PK (100 PK)

35.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=30mm, B=35mm, C=28mm, D=31mm, E=16mm, F=37mm	OR orange	1 PK (100 PK)
36.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=47mm, B=50mm, C=45mm, D=48mm, E=17mm, F=60mm	OR orange	1 PK (100 PK)

37.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=65mm, B=68mm, C=63mm, D=67mm, E=18mm, F=73mm	OR orange	1 PK (100 PK)
38.	Tapered Caps & Plugs	 	Caps for external and internal NPT fittings. Can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (flexible) polythene they can be applied to fit snugly and are easily removable. Size A=83mm, B=90mm, C=81mm, D=89mm, E=28mm, F=94mm	OR orange	1 PK (100 PK)
39.	Wristband Paracord With Attachment Points		High-Visibility orange paracord with barrel lock adjustment feature. Attachments include an extra barrel lock, clip, or clamp.	OR orange	10 pcs (Each)

40.	Parts Bags			Parts bags with fastening strap 6in diameter x 10in (15cm x 25cm)	OR Orange	10 pcs (Each)
41.	Cable Ties Speedwrap Hook & Loop			Industrial strength die-cut Hook & Loop Ties. Reusable and adjustable fastening solution. 0.5in x 6in (1.2cm x 5.7cm)	Yellow	1 PK (100 PK)
42.	Cable Ties Speedwrap Hook & Loop			Industrial strength die-cut Hook & Loop Ties. Reusable and adjustable fastening solution. 0.75in x 15in (1.2cm x 38cm)	Yellow	1 PK (100 PK)
43.	Floating Cable Ties			Floating Cable Ties Polypropylene No metal components Tensile strength at 73° F: 50lb (for all sizes) 74 Radiation Resistance (Rads): 1x106	OR Orange	1 PK (250 PK)

APPENDIX 1

			Max. continuous use temperature: 239° F (115° C) Min. application use temperature: -76° F (-60° C/ 11.4 in (27cm)		
44.	FME Hammer		Shot-free Dead Blow Hammer Shock-resistant. Encapsulated head, weight 3lb(1.361kg)	Green	5 pcs (Each)
45.	FME Hammer		Shot-free Dead Blow Hammer Shock-resistant. Encapsulated head, weight 8lb(3.62kg)	Green	5 pcs (Each)
46.	FME Hammer		Shot-free Dead Blow Hammer Shock-resistant. Encapsulated head, weight 12lb(5.44kg)	Green	5 pcs (Each)
47.	Swivel D-Ring		Swivel D-Ring With Cord It can be used to quickly cinch tools up to 10 lbs (4.5 kg). Swivel at D-ring makes the tool tangle-resistant.	OR Orange	1 PK 10 PK

APPENDIX 1

48.	Premium wristband		Wristband with retractable cord, trigger, plastic grommet, and adjustable hook and loop comfort strap. (Also available without trigger)	As in the photo without color choice	3 pcs (Each)
49.	Magnetic Retrieval Tools		Flex Magnetic Pick-Up Tool with Powercap reduces interference and accidental sticking to unwanted surfaces with maximum lifting weight 2.27 kg. Length 736MM	As in the photo without color choice	3 pcs (Each)
50.	Wrist Band with Cord and Clip		Economy wrist tether with an adjustable Velcro strap and high-visibility orange fabric.	OR Orange	1 PK 10 PK
51.	Wrist Band with Cord and Barrel Lock		Economy wrist tether with an adjustable Velcro strap and high-visibility orange fabric and barrel lock.	OR Orange	1 PK 10 PK
52.	belt		44in-52in (112cm-132cm)	1 pcs (Each)	
53.	belt		36in-44in (91cm-112cm)	1 pcs (Each)	

54.					1 pcs (Each)
55.	Non-floating wristband tether			Non-floating tether for everyday use.	3 pcs (Each)